



# CLOPAY® SELECTION CHART

## UPWARD ACTING SECTIONAL DOORS

### NON-INSULATED STEEL DOORS

Model Number	Gauge	Face Design	WINDCODE®**	Glazing	Pass Door	Specialized Track					Std Max Size*
						Low Hdrm	High Lift	Vert Lift	Follow Roof	High Cycle	
525	25	Deep Rib	W4, W6	Yes	n/a	Yes	Yes	Yes	Yes	Yes	20'2" x 16'
524	24	Deep Rib	W4, W5, W6, W8	Yes	Up to 14' wide**	Yes	Yes	Yes	Yes	Yes	24' x 20'
692	24	Raised Panel	W4	Yes	n/a	Yes	Yes	Yes	Yes	Yes	18' x 16'
520	20	Deep Rib	W4, W5, W6, W8	Yes	Up to 16' wide**	Yes	Yes	Yes	Yes	Yes	26' x 20'
616	16	Flush	Consult Technical Services	Yes	n/a	Yes	Yes	Yes	Yes	Yes	24' x 18'

\*Consult Technical Services for maximum WINDCODE sizes and for larger size doors.

\*\*Not available with WindCode models.

WINDCODE®** Key		
	Design Load PSF	Test Load PSF
W4	23 - 28	34 - 42
W5	29 - 36	43 - 54
W6	37 - 40	55 - 60
W8	46 - 54	69 - 81

Maximum sizes vary by model and windload.

